

Grating

Grating

Grating				
Reflective planar line diffraction				
Features Up to 80% efficiency. Bri		General specifications of light gr		
Model	Number of inscriptions (l/mm)	Shine wavelength (nm)	Shine Corner	Size (mm)
G-600-250-12.7	600	250	4°18'	12.7 2 ×6
G-600-500-12.7	600	500	8°37'	25 2 ×10
G-600-500-25	600	500	8°37'	25 2 ×10
G-600-640-25	600	640	11°4'	12.7 2 ×6
G-600-750-12.7	600	750	13°0'	12.7 2 ×6
G-600-750-25	600	750	13°0'	25 2 ×10
G-600-1000-25	600	1000	17°27'	25 2 ×10
G-1200-250-25	1200	250	8°37'	25 2 ×10
G-1200-300-12.7	1200	300	10°22'	12.7 2 ×6
G-1200-500-25	1200	500	17°27'	25 2 ×10
G-1200-640-25	1200	640	22°35'	25 2 ×10
G-1200-750-25	1200	750	26°44'	25 2 ×10
G-1200-1000-25	1200	1000	36°52'	25 2 ×10
G-1800-250-12.7	1800	250	13°0'	12.7 2 ×6
G-1800-300-25	1800	300	15°40'	25 2 ×10
G-1800-500-25	1800	500	26°44'	25 2 ×10
G-2400-250-12.7	2400	250	17°27'	12.7 2 ×6
G-2400-250-25	2400	250	17°27'	25 2 ×10
G-3600-200-25	3600	200	21°6'	25 2 ×10