

DPS-1064-D/1-10mJ

SPECIFICATIONS



**HIGH ENERGY DIODE
PUMPED ALL-SOLID-STATE
Q-SWITCHED LASER**

High energy diode pumped all solid state Q-switched laser at 1064nm has the features of high single pulse energy, short pulse duration, and high peak power, which is widely used in LIBS, LIF, ICP-MS, LCD repair, scientific research, and so on.



Wavelength (nm)	1064±1	
Operating mode	Actively	
Single pulse energy (mJ)	1-5	5-10
Pulse duration (ns)	<10	
Jitter (ns, sdev)	<1ns (Int.)	
Rep. rate ¹	1-100Hz (adjustable)	
Energy stability (std dev/mean)	<3%, <2%, <1%	
Beam diameter (mm)	~1	~2
Beam divergence, full angle (mrad)	≤3	
M ²	≤1.5	
Warm-up time (minutes)	<15	
Beam height from base plate (mm)	98.5	
Cooled method	Air cooled	
Operating temperature (°C)	15-35	
Operating voltage (VDC)	24V/18.8A	
Expected lifetime (pulses)	10 ⁹	



LASER HEAD (Driver integrated)	POWER SUPPLY (110/220VAC) optional
 415(L)×202(W)×139(H)mm³, 22 kg	 225(L) ×134(W) ×35(H) mm³, 0.85 kg

¹ Both internal trigger and external trigger are acceptable.

Website: <http://www.cnilaser.com> E-mail: sales@cnilaser.com Tel: +86-431-85603799 Fax: +86-431-89216068