

DPS-527-Q/1-20mJ

**HIGH ENERGY DIODE PUMPED
ALL-SOLID-STATE
Q-SWITCHED LASER**

High energy diode pumped all solid state Q-switched laser at 527nm has the features of high single pulse energy, high output power, and high peak power, which is widely used in pumping Ti:Sapphire laser, semiconductor water surface processing, PIV, flow field lighting imaging, scientific research, and so on.




SPECIFICATIONS

Wavelength (nm)	527±1
Operating mode	Actively
Single pulse energy (mJ)	1-20@1kHz
Average power (W)	1-20@1kHz
Pulse duration (ns)	~200@1kHz
Rep. rate ¹	0.2-10kHz
Mode	Multi-Mode
Power stability (rms)	<2%, <1%, <0.5%
Beam divergence, full angle (mrad)	~5
Beam diameter (mm)	~5
Pointing stability over temperature (urad/°C)	<50
Warm-up time (minutes)	<15
Beam height from base plate (mm)	95
Cooled method	Water cooled
Operating temperature (°C)	15-35
Power supply (110/220VAC)	PSU-DPS-Q
Expected lifetime (hours)	>10000
Available options	Articulated arm; Laser light sheet; Double pulse function: adjustable pulse interval of 100 ~ 400us




LASER HEAD




556 (L) × 264 (W) × 131 (H) mm³, 17.7kg

POWER SUPPLY



370 (L) × 483 (W) × 89.5 (H) mm³, 6.8kg

WATER CHILLER (WCH-3500)



510 (L) × 452 (W) × 976 (H) mm³, 60 kg

¹ Both internal trigger and external trigger are acceptable. One fixed value between 0.2~10kHz.

Website: <http://www.cnilaser.com> E-mail: sales@cnilaser.com Tel: +86-431-85603799 Fax: +86-431-89216068