

DPS-532-G/30-150mJ

SPECIFICATIONS




**HIGH ENERGY DIODE PUMPED
ALL-SOLID-STATE
Q-SWITCHED LASER**

High energy diode pumped all solid state Q-switched laser at 532nm has the features of high single pulse energy, high repetition rate, short pulse duration, and high peak power, which is widely used in ladar, pumped dye laser, material impact strengthening, scientific research, and so on.



Wavelength (nm)	532±1
Operating mode	Actively
Single pulse energy (mJ)	30-150
Pulse duration (ns)	<10
Jitter (ns, sdev)	<1ns (Int.)
Rep. rate ¹	100Hz
Energy stability (std dev/mean)	<5%, <3%, <2%
Beam divergence, full angle (mrad)	<3
Beam diameter (mm)	~7.5
Warm-up time (minutes)	<15
Beam height from base plate (mm)	108
Cooled method	Water cooled
Operating temperature (°C)	15-35
Power supply (110/220VAC)	PSU-DPS-G
Expected lifetime (pulses)	10 ⁹
Available options	Attenuator



LASER HEAD	POWER SUPPLY ²	WATER CHILLER (WCH-2700)
 800 (L) × 266 (W) × 150 (H) mm³, 48 kg	 700 (L) × 483 (W) × 221 (H) mm³, 30 kg	 463 (L) × 647.5 (W) × 897 (H) mm³, 55kg

1 Both internal trigger and external trigger are acceptable.

2 Energy can be adjusted by touch screen.

Website: <http://www.cnilaser.com> E-mail: sales@cnilaser.com Tel: +86-431-85603799 Fax: +86-431-89216068