

EO-213-Subnano/1-30μJ/1-30mW


HIGH ENERGY DIODE PUMPED ALL-SOLID-STATE Q-SWITCHED LASER

High energy diode pumped all solid state Q-switched laser at 213nm has the features of high single pulse energy, short pulse duration, and high peak power, which is widely used in biomedicine, environmental monitoring, scientific research, and so on.




SPECIFICATIONS

Wavelength (nm)	213±1nm
Operating mode	Actively
Single pulse energy (uJ)	1-30uJ@1kHz
Average power (mW)	1-30mW@1kHz
Power stability (rms, 4 hours ±3°C)	<5%
Pulse duration (ns)	<2ns@1kHz
Rep. rate ¹	1-5kHz
Beam diameter (mm)	~1.5mm
Beam divergence, full angle (mrad)	<5mrad
Warm-up time (minutes)	<15
Beam height from base plate (mm)	101
Cooled method	Air cooled
Operating temperature (°C)	15-30
Power supply (110/220VAC)	PSU-EO-Subnano




LASER HEAD



434.5(L)×160(W)×145(H)mm³, 10kg

POWER SUPPLY



391(L)×344(W)×120.5(H)mm³, 10kg

¹ Repetition rate 1-5kHz variable, adjust the step size to 1kHz.

Website: www.precisometer.com E-mail: info@precisometer.com