

HPL-1319-Q/20-50W

**WATER COOLING LD PUMPED
ALL-SOLID-STATE Q-SWITCHED
INFRARED LASER at 1319nm**





All solid state Q-switched infrared laser at 1319nm has the features of high peak power, high repetition rate, and short pulse duration, which is widely used in marking, carving, measure, science research, and so on.



SPECIFICATIONS

Wavelength (nm)	1319±1
Operating mode	Actively
Average power (W) ¹	20-50
Pulse duration (ns)	~250 @10kHz&50W
Rep. rate ²	10-20 kHz
Single pulse energy (mJ)	2-5
Peak power (kW)	8-20 @10kHz
Ave power stability (rms, 4 hours±3°C)	<5%, <3%
Beam divergence, full angle (mrad)	<3.5
Beam diameter at the aperture (1/e2,mm)	<12
Beam height from base plate (mm)	55
Warm-up time (minutes)	<10
Cooled method	Water Cooled
Operating temperature (°C)	15-35
Power supply (220-240AC)	PSU-HPL-Q & PSU-HPL-CW
Expected lifetime (hours)	>10000



LASER HEAD	POWER SUPPLY	POWER SUPPLY	WATER CHILL
 417.5 (L) ×150(W) ×130(H) mm³, 7.5kg	 282(L) ×483(W) ×88(H) mm³, 7.5kg	 288(L) ×482(W) ×90(H) mm³, 5.5kg	 475 (L) ×575(W) ×805(H) mm³, 60kg

1 Any power level can be selected in this range.

2 Other rep.rate range available on request.

Website: <http://www.cnilaser.com> E-mail: sales@cnilaser.com Tel: +86-431-85603799 Fax: +86-431-89216068