

LPS-L-1064/350~1000mJ

SPECIFICATIONS




HIGH ENERGY LAMP PUMPED SOLID STATE Q-SWITCHED LASER

High energy lamp pumped solid state Q-switched laser at 1064nm has the features of high single pulse energy , short pulse duration , and high peak power , which is widely used in PIV, LIF, LIBS, ICP-MS, Raman , scientific research, military ,and so on.



Wavelength (nm)	1064±1			
Operating mode	Q-switched: EOM (Electro-optic modulation)			
Single pulse energy (mJ)	350	500	700	1000
Pulse duration (ns)	<10	<10	<8	<8
Rep. rate (Hz)	1~10 (adjustable)			
Energy stability	<3%			
Beam divergence, full angle (mrad)	~1	~1	~1	~3
Beam diameter (mm)	7	8	8	9
Warm-up time (minutes)	<15			
Beam height from base plate (mm)	80			
Cooled method	Water Cooled			
Operating temperature (°C)	15~35			
Power supply (220/110VAC)	PSU-LPS-L(3U)			
Expected lifetime (pulses)	10 ⁷ ~10 ⁸			
Warranty period	1 year			
Available Options	SHG Module ;Higher Repetition Rates:≤20Hz ; Jitter:~1ns (Sdev)			



LPS-L-1064	PSU-LPS-L (3U)	Water Chiller
 600 (L) ×245(W) ×130(H) mm³, 24kg	 480 (L) ×505(W) ×135(H) mm³, 16 kg Rep. Rate and Voltage can be adjusted by touch screen	 580(L) ×290(W) ×470(H) mm³, 24 kg

Website: www.precisometer.com E-mail: info@precisometer.com