



MDL-H-2160/1~400mW



INFRARED DIODE LASER
AT 2160nm

It features ultra compact design, long lifetime, cost-effectiveness and easy operation. They are used in measurement, communication, spectrum analysis, etc.



SPECIFICATIONS

Central wavelength (nm)	2160±20	
Operating mode	CW	
Output power (mW)	>1, 100, 200, ... ,400	
Power stability (rms, over 4 hours)	<1%, <2%, <3%	
Transverse mode	Multimode	
Dimensions of beam at the aperture (mm)	~7×8	
Beam divergence, full angle (mrad)	<5. 0	
Warm-up time (minutes)	<5	
Beam height from base plate (mm)	29	
Operating temperature (°C)	10~35	
Power supply (100-240VAC)	PSU-H-LED	PSU-H-FDA
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz optional	
Expected lifetime (hours)	10000	
Warranty	1 year	



MDL-H-2160	PSU-H-LED	PSU-H-FDA
160 (L) × 77 (W) × 60 (H) mm³, 0.9kg	277 (L) × 145 (W) × 106 (H) mm³, 2.3kg	275 (L) × 145 (W) × 104 (H) mm³, 2.1kg