

MGL-N-588/300-500mW




LD PUMPED ALL-SOLID-STATE
YELLOW LASER AT 588nm





All solid state laser at 588nm is made features of ultra compact, long lifetime and easy operating, which is used in scientific experiment, optical sensor, measurement, instrument, communication, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	588±2
Operating mode	CW
Output power (mW) ¹	300-500
Power Stability (rms, 4 hours ± 3°C)	<3%, <2%, (<1% optional)
Transverse mode	Near TEM ₀₀
M ²	<3.0
Beam divergence, full angle (mrad)	<1.5
Beam diameter at the aperture (1/e ² , mm)	~3.0
Warm-up time (minutes)	<10
Polarization ratio	>50:1(100:1 optional) , Horizontal(Vertical optional)
Pointing Stability(urad) (over 2 hours after warm-up and ±3°C)	<50
Pointing Stability Over Temperature (urad/°C)	<20
Beam height from base plate (mm)	68.4
Operating temperature (°C)	10-35
Power supply (100-240VAC)	PSU-H-FDA/PSU-H-LED/PSU-H-OEM
Modulation option	DC-1kHz, 1kHz-10kHz, 10kHz-30kHz optional; TTL and Analog optional
Expected lifetime (hours)	>10000



LASER HEAD	POWER SUPPLY (PSU-H-FDA) ²	POWER SUPPLY (PSU-H-LED) ³	DRIVER (PSU-H-OEM)
 245 (L) × 99 (W) × 94 (H) mm³, 2.6 kg	 275.5 (L) × 145 (W) × 106 (H) mm³, 2.5 kg	 275.5 (L) × 145 (W) × 106 (H) mm³, 2.5 kg	 182 (L) × 140.5 (W) × 52 (H) mm³, 0.85 kg

1 Any power level can be selected in this range.

2 Fixed output power.

3 Output power adjustable 10-100%.