

MGL-W-577A/1.2-5W




LD PUMPED ALL-SOLID-STATE
YELLOW LASER AT 577nm

All solid state 577 nm yellow laser is made features of ultra compact, long lifetime and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, etc.




SPECIFICATIONS

Model	MGL-W-577A	MGL-W-577A-II
Wavelength (nm)	577±2	
Operating mode	CW	
Output power (W) ¹	1.2-3	3-5
Power Stability (rms, 4 hours ± 3°C)	<3%, <2%, (<1% optional)	
Transverse mode	Near TEM ₀₀	
Beam divergence, full angle (mrad)	<1.5	
Beam diameter at the aperture (1/e ² , mm)	~5.0	
Warm-up time (minutes)	<10	
Pointing Stability(urad) (over 2 hours after warm-up and ±3°C)	<50	
Pointing Stability Over Temperature (urad/°C)	<20	
Polarization ratio	>50:1(100:1 optional) , Horizontal(Vertical optional)	No polaritio
Beam height from base plate (mm)	80	80
Operating temperature (°C)	10-35	
Power supply (100-240VAC)	PSU-W-LED	PSU-AOM
Modulation option	DC-1kHz, 1kHz-10kHz, 10kHz-30kHz optional; TTL and Analog optional	
Expected lifetime (hours)	>10000	




LASER HEAD (MGL-W-577A)




305 (L) × 120 (W) × 103 (H) mm³, 5.4 kg

LASER HEAD (MGL-W-577A-II)




357 (L) × 240 (W) × 108 (H) mm³, 11.6 kg

POWER SUPPLY (PSU-W-LED)



301.5 (L) × 185 (W) × 114 (H) mm³, 3.0 kg

POWER SUPPLY (PSU-AOM)



379.1(L) × 248 (W) × 136.1 (H) mm³, 7.7kg