

OEM-N-532/3~5W



LD PUMPED ALL-SOLID-STATE GREEN LASER MODULE CORE


All solid state 532nm green laser module core is made features of ultra compact, long lifetime and easy operating. It's easy to be integrated into customer's equipment.







SPECIFICATIONS

Wavelength (nm)	532±1
Operating mode	CW
Output power (W)	>3, 3.5, 4, ..., 5
Power stability (rms, over 4 hours) at 25℃	<3%, <5%
Transverse mode	Near TEM ₀₀
Beam divergence, full angle (mrad)	<1.0
Beam diameter at the aperture (mm)	~3.0
Warm-up time (minutes)	<10
Beam height from base plate (mm)	30
Operating temperature (℃)	22.5+/-2.5
Driver (12VDC 25A)	PSU-OEM-N (key switch and emergency stop are available on request)
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz optional
Expected lifetime (hours)	10000
Warranty period	1 year

Note: The laser needs to be used on a heat sink with good heat dissipation.



OEM-N-532	PSU-OEM-N		Accessory (Power supply 100-240VAC)
	A heat dissipation	No heat dissipation	
 212 (L) × 70 (W) × 52.6 (H) mm³, 1.4 kg	 198 (L) × 100 (W) × 61 (H) mm³, 0.7 kg	 190 (L) × 70 (W) × 34 (H) mm³, 0.4 kg	 12VDC 25A: 199 (L) × 99 (W) × 50 (H) mm³, 0.9 kg

Website: www.precisometer.com E-mail: info@precisometer.com