

Optical Table Accessories and Application Examples

OTSB-HD100 Handles for Aluminum Breadboard



- Installation spacing: 100mm, fixed by M6 screw
- Load of handle: 30Kg
- Note: We do not recommend that you use the handles for ferromagnetic stainless steel breadboards or optical table.

RBP Rubber Mat



- Material: Rubber
- Thickness: <5mm
- Application: spacer, reduce vibration

Selection Table:

Model	Item name	L×W×H(mm)
RBP100100-5	Rubber Mat	100×100×5
RBP200200-5	Rubber Mat	200×200×5


RBL Rubber Foot



- Material: Rubber

Selection Table:

Model	Item name	Notes
RBL	Rubber foot	1set 4pcs



Air Compressor



Model	TW550-4C
Exhaust volume	35L /min
Exhaust pressure	0.1 ~0.8MPa
Voltage frequency Volt./ Hz	220V 50Hz
Power HP/W	550W
Speed(R.P.M)	1450
Running Noise(dB)	51±3
Tank (Lt)	4
Net weight(KG)	23
Size LxWxH mm	460x210x480

Air Compressor



Model	TW5501
Exhaust volume	115-30L/min
Exhaust pressure	0.1 ~0.8MPa
Voltage frequency Volt./ Hz	220V 50Hz
Power HP/W	550W
Speed(R.P.M)	1450
Running Noise(dB)	62±3
Tank (Lt)	25
Gross weight(KG)	35
Net weight(KG)	25
Size LxWxH mm	408x408x530