

# 660nm Fiber Coupled FP Laser Source

Single mode, up to 30mW, 2nm, Benchtop or Module



DATASHEET

[Return to the Webpage](#)



Agiltron provides cost-effective fiber-coupled laser sources with a wide range emitting spectrum from 370nm to 2000nm and line width from 10kHz to broadband to select. Each benchtop laser source features a pigtailed laser and high-precision, low-noise auto-feedback drive electronics to ensure constant output power or a constant driving current, and an integrated temperature control unit maintains optimal operating conditions. Each unit features a front fiber output connector and a universal power supply compatible with 100 to 240 VAC. We offer two packages: benchtop for ease of use and compact module for system integration. The user interface benchtop includes an intuitive LCD display for independent control of output power and temperature via two front rotating knobs. The module has two front output power and temperature settings. All units have a built-in isolator option to prevent reflection-induced laser emissions instability. We produce fiber-coupled isolators from 370nm to 2000nm. An isolator is essential to obtain stable laser output.

## Specifications

| Parameter                          | Min | Typical | Max | Unit |
|------------------------------------|-----|---------|-----|------|
| Threshold Current                  | -   | 45      | 65  | mA   |
| Operating Current                  | SM  | 120     | 140 | mA   |
|                                    | PM  | 140     | 160 |      |
| Operating Voltage                  | -   | 2.5     | 3.2 | V    |
| Optical Output Power               |     | 30      |     | mW   |
| Center Wavelength@25°C             | 650 | 660     | 670 | nm   |
| Spectral Linewidth (FWHM)          |     |         | 2   | nm   |
| Polarization Extinction Ratio (PM) | 14  | 16      | 20  | dB   |
| Monitor Current                    |     | 0.3     |     | mA   |
| Reverse Voltage                    |     |         | 30  | V    |
| Recommend Operating Temperature    |     | 25      |     | °C   |
| Operating Case Temperature         | -10 |         | 70  | °C   |
| Storage Temperature                | -40 |         | 85  | °C   |

## Features

- Turnkey Laser Source
- High Stability
- Advanced Feedback Control

## Applications

- Medical Laser Treatment
- Biotechnology
- Others



**Note:** The specifications provided are for general applications with a cost-effective approach. If you need to narrow or expand the tolerance, coverage, limit, or qualifications, please [click this link](#):

Rev 09/20/25

© Photonwares Corporation

P +1 781-935-1200

E [sales@photonwares.com](mailto:sales@photonwares.com)

W [www.agiltron.com](http://www.agiltron.com)

Information contained herein is deemed to be reliable and accurate as of the issue date. Photonwares reserves the right to change the design or specifications at any time without notice. Agiltron is a registered trademark of Photonwares Corporation in the U.S. and other countries.

# 660nm Fiber Coupled FP Laser Source

Single mode, up to 30mW, 2nm, Benchtop or Module



## DATASHEET

### Benchtop Laser Source Operation Manual



- Plug in power cable
- Turn on Power Switch
- Setting the Output Power by rotating the knob
- Setting the laser diode Temperature by rotating the knob
- Connect a fiber path cable with matching connector (FC/APC is the default)
- Push the Emission switch to turn on the laser
- Measure the output power to verify

### Module Laser Source Operation Manual



- Plug in power cable
- Turn on Power Switch
- Setting the Output Power by rotating the screw
- Setting the laser diode Temperature by rotating the screw
- Connect a fiber path cable with matching connector (FC/APC is the default)
- Push the Emission switch to turn on the laser
- Measure the output power to verify


# 660nm Fiber Coupled FP Laser Source

Single mode, up to 30mW, 2nm, Benchtop or Module





## DATASHEET

### Module (mm): Plug-Play (Power Supply Included)



### Benchtop (mm): Plug-Play 100-240VAC, USB



\*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

© Photonwares Corporation

P +1 781-935-1200

E [sales@photonwares.com](mailto:sales@photonwares.com)

W [www.agiltron.com](http://www.agiltron.com)

Information contained herein is deemed to be reliable and accurate as of the issue date. Photonwares reserves the right to change the design or specifications at any time without notice. Agiltron is a registered trademark of Photonwares Corporation in the U.S. and other countries.


# 660nm Fiber Coupled FP Laser Source

Single mode, up to 30mW, 2nm, Benchtop or Module



## DATASHEET

### Typical Spectrum



### Ordering Information (Part Number)

| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/>   | <input type="checkbox"/> | <input type="checkbox"/>                   | <input type="checkbox"/> | <input type="checkbox"/>                                        | <input type="checkbox"/>                                                                                |
|--------------------------|--------------------------|--------------------------|--------------------------|----------------------------|--------------------------|--------------------------------------------|--------------------------|-----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| Prefix                   | Wavelength               | Power                    | Linewidth                | Package                    | Isolator                 | Control Mode                               | TEC Cooling              | Fiber Type                                                      | Connector <sup>[1]</sup>                                                                                |
| FCLS-                    | 660nm = 0660             | 30mW = B                 | 2nm = 1                  | Benchtop = 1<br>Module = 2 | None = 1<br>Yes = 2      | Constant Current = 2<br>Constant Power = 1 | No = 1<br>Yes = 2        | SM450 = 3<br>SM600 = 6<br>PM460 = B<br>PM630 = C<br>Special = 0 | FC/APC = 3<br>FC/PC = 2<br>Non = 1<br>SC/PC = 4<br>SC/APC = 5<br>LC/PC = 7<br>LC/UPC = U<br>Special = 0 |

[1]. The default connector configuration uses fiber with 0.9 mm buffer protection. The connector cannot be installed directly onto bare fiber because the bare fiber is prone to damage during shipping. However, the connector can be assembled on bare fiber if a 3 cm protective loose tube is added for reinforcement. The customer may remove this protective tube after testing. The optical power handling of a standard connector is less than 0.5 W for SMF-28 fiber and decreases further for smaller-core fibers.