

Fiber Optical Phase Modulator

10 GHz, 1310 nm



DATASHEET

[Return to the Webpage](#)



Features

- 10GHz Bandwidth
- X-cut APE Process
- Low Insertion Loss
- Low Drive Voltage
- 1270 nm to 1370 nm
- Minimal Back Reflections
- Chip PER over 60dB

Applications

- Optical Chirping
- Research & Development
- Laser Linewidth Broadening
- FM Spectroscopy
- Frequency Shifting



Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.

Rev 07/09/26

The LNPM is a high-performance, fiber-coupled phase modulator with operating frequencies ranging from DC to 10GHz, covering the 1270-1370 nm wavelength band. It is constructed using optical waveguides on high efficient X-cut LiNbO₃ material and is coupled with polarization-maintaining input and output fibers.

Note: This component is intended for OEM system integration and is not designed for standalone laboratory use. Units supplied without a protective benchtop enclosure are provided without warranty, as they are susceptible to damage from improper handling, installation, or operation.

Specifications

Parameter	Min	Typical	Max	Unit
Input Optical Power			50	mW
Operating Wavelength	1270		1370	nm
Insertion Loss			4	dB
Polarization Extinction Ratio	20			dB
Optical Return Loss	30			dB
S21 Bandwidth		8	10	GHz
V _π @10GHz		8.8		V
RF Input Power			30	Vpp
Impedance		50		Ω
Operating Temperature	-55	8.8	75	°C
Storage Temperature	-60		90	°C
Operating Humidity	0	50	90	%

[+1 781-935-1200](tel:+17819351200)

sales@agiltron.com

www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice.
Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.


Fiber Optical Phase Modulator

10 GHz, 1310 nm



DATASHEET

Dimensions (mm)



Unit: mm

*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

Electrical Connection

PIN	Symbol	Description
1	-	N/A
2	-	N/A
3	-	N/A
4	-	N/A
5	-	N/A
6	-	N/A
7	-	N/A
RF	RF connector*	K Connector

Ordering Information (Part Number)

	2	1	☐	☐	☐	☐	☐	☐	☐
Prefix	Configuration	Wavelength	Frequency	Input Fiber	Output Fiber	Cable	Fiber Length	Connector ^[1]	
LNPM-	Phase = 2	1310nm = 3	10GHz = 2	PM 1310 = 3	PM 1310 = 3	0.9mm Tube = 1	0.5m = 1 Special = 0	FC/APC = 3 FC/PC = 2 Special = 0	

[1]. The default connector configuration uses fiber with 0.9 mm buffer protection. The connector cannot be installed directly onto bare fiber because the bare fiber is prone to damage during shipping. However, the connector can be assembled on bare fiber if a 3 cm protective loose tube is added for reinforcement. The customer may remove this protective tube after testing. The optical power handling of a standard connector is less than 0.5 W for SMF-28 fiber and decreases further for smaller-core fibers.


Fiber Optical Phase Modulator

10 GHz, 1310 nm



 DATASHEET

Vp vs Frequency



Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice.
Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.