

Ultra-High Voltage Sensor Optical Means of High Reliability

SM, PM, MM



DATASHEET

[Return to the Webpage](#)



Features

- Up To 300kV
- High Accuracy: $\pm 0.5\%$
- Temperature Independent Measurement
- Zero Phase Shift
- Self-Powered
- Bluetooth Data Interface
- Lightweight
- Cost Effective LED System

Specifications

Parameter	Min	Typical	Max	Unit
Measured Voltage		up to 250		kV
Voltage Accuracy		$< \pm 2$		%
Frequency Response	0.05		5	kHz
Phase Shift		0		
Insulation Class		35		kV
Power		Self		
Communication		Bluetooth		
Operating Temperature	-45		65	°C
Weight		2		lbs
Conductor Diameter Range	0.25		2	inch

Based on a patent-pending optical sensor design, the High Voltage Sensing System (HVSS) offers a reliable, safe, and precise method for measuring ultra-high voltages. The sensor is a fully passive device, interrogated via a single optical fiber, making it inherently immune to damage in high-voltage environments. Designed for direct mounting onto high-voltage conductor lines, the HVSS delivers key advantages: highly accurate voltage measurement independent of temperature variations, zero phase shift, low-noise flat frequency response up to the 20th harmonic, lightweight construction, and cost-effective optical readout.

The standard readout system is a benchtop unit with remote connectivity via USB, RS232, Ethernet, or wireless interfaces, and supports power inputs of 5VDC or 100–240VAC. An optional all-in-one customer unit is available, featuring a cable-mountable sensor with an integrated inductive energy harvester and Bluetooth communication to a nearby transmission unit—eliminating the need for external power or physical connectivity.



Note: The specifications provided are for general applications with a cost-effective approach. If you need to narrow or expand the tolerance, coverage, limit, or qualifications, please [\[click this link\]](#):

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.

Rev 08/17/25

© Photonwares Corporation

P +1 781-935-1200

E sales@photonwares.com

W www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. Photonwares reserves the right to change the design or specifications at any time without notice. Agiltron is a registered trademark of Photonwares Corporation in the U.S. and other countries.

Ultra-High Voltage Sensor Optical Means of High Reliability

SM, PM, MM



DATASHEET

Ordering Information (Part Number)

	□ □ □	□	1	1	□ □	□	1
Prefix	Type	Voltage			Readout	Conductor Diameter	
HVSS-	Standard = 300 Special = 000	15kv = 1 25kV = 2 35kV = 3 45kV = 4 60kV = 6 70kV = 7 Special = 0			Benchtop USB = SB Benchtop RS232 = RS Benchtop Ethernet = ET Benchtop Bluetooth = BL Special = 00	0.25 inch = 1 0.45 inch = 2 0.65 inch = 3 0.85 inch = 4 1.05 inch = 5 1.25 inch = 6 1.45 inch = 7 1.65 inch = 8 1.85 inch = 8 2 inch = 9	

Red is special order