

100G Transmultiplexer Unit TMUX OTU



DATASHEET

[Return to the Webpage](#)



The TMUX3800 100G is a high-performance optical networking board designed to maximize fiber efficiency by aggregating diverse client-side traffic into a single high-speed transport stream. It functions as a Transmultiplexer (TMUX) that grooms multiple lower-rate signals—such as 10G or 40G Ethernet—and maps them into a unified 100G OTN (Optical Transport Network) container for seamless long-haul transmission. By integrating Optical Transform Unit (OTU) capabilities, the card converts standard "grey" client signals into specialized "colored" DWDM wavelengths, ensuring robust delivery across optical backbones. This solution is particularly notable for its high-density architecture and low power consumption of 30W or less, making it an efficient choice for scaling bandwidth in metro and long-haul data center interconnect applications.

Features

- 100G Line Throughput
- Service Aggregation
- Standardized Mapping
- Wavelength Conversion
- Plug-in card design, easy expansion
- Low Power Consumption

Applications

- DWDM Network
- Data Center Network

Specifications

Parameter		Specification		Unit
Data Rate			100	Gbps
Center Wavelength (DWDM)		1529.50	1565.50	nm
100G interface	Client Side	100G QSFP28 module		
	Line Side	4xSFP28 25G module		
NMS		TELNET, SNMP, WEB		
Power Consumption		≤ 30		W
Operating Temperature		-10	+60	°C
Storage Temperature		-40	+80	°C
Relative Humidity		5% ~ 95% Non-condensing		

Note: The specifications provided are for general applications with a cost-effective approach. If you need to narrow or expand the tolerance, coverage, limit, or qualifications, please [click this link](#):

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.

Rev 04/28/26



+1 781-935-1200

sales@agiltron.com

www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice. Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.

100G Transmultiplexer Unit TMUX OTU



DATASHEET

Layout (1 Slot, 100G)



Ordering Information (Part Number)

	☐	☐	☐	☐	☐	☐
Prefix	Model	SFP28 #	QSFP28	1	1	Rack
TMUX-	SFP = 01 QSFP+ = 04 QSFP28 = 10 Special = 000	1 = 1 2 = 2 3 = 3 4 = 4	Yes = 1 Non = N			Non = N 1U Ethernet = 1 2U Ethernet = 2 3U Ethernet = 3 4U Ethernet = 4

P +1 781-935-1200

E sales@agiltron.com

W www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice.
Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.