

Passive Fiber Mode Scrambler/De-Speckler

No-Speed limitation, Fiber Core 50-105 μm , Wavelength 300 to 2600 nm, 10W



[Return to the Webpage](#)



The PFMS is an all-fiber passive mode homogenizer designed to overcome the modulation speed limitations of mechanical mode scramblers and to operate reliably with high-power pulsed lasers. Leveraging a proprietary patent-pending design, the PFMS incorporates a mode-homogenizing element between two multimode fibers to redistribute the optical field within the fiber core. This passive scrambling process stabilizes the beam profile and suppresses modal interference. In multimode fibers, mode field fluctuations can introduce signal instability, speckle, and modal noise. The PFMS eliminates these effects by delivering a stable, homogeneous output, ensuring accurate and repeatable results. It is ideally suited for applications demanding uniform beam quality without modulation speed limitation, such as life sciences, digital laser projection, interferometry, laser beam homogenization, lithography, metrology, and fiber-based sensor systems. Compact and plug-and-play, the PFMS is engineered for seamless integration into fiber-coupled assemblies, providing robust despeckling and long-term reliability in demanding environments including space deployment. The standard configuration is designed to handle up to 5W optical power. Special version is cable up to 50W optical power with liquid internal cooling technology.

Features

- High Power
- Low Cost
- High Stability
- High Reliability
- Wide Temperature Operation

Applications

- Test/Measurement
- Sensor Systems
- Instruments




Specifications

Parameter	Min	Typical	Max	Unit
Wavelength	300		2600	nm
Insertion Loss ^[1]	0.5	1	2	dB
Optical Power Handling		5	50	W
Return Loss	50			dB
Operating Temperature	-20		100	°C
Storage Temperature	-40		85	°C
Fiber Diameter	50		400	μm


Notes:

[1] Without a connector, each connector adds 0.3dB

Beam Spot Before and After Homogenization



■ Without Scrambler



■ With Scrambler

Rev 05/07/26

P +1 781-935-1200

E sales@agiltron.com

W www.agiltron.com


Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice.
Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.

Passive Fiber Mode Scrambler/De-Speckler

No-Speed limitation, Fiber Core 50-105 μm , Wavelength 300 to 2600 nm, 10W



Mechanical Dimensions (mm)



*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

Ordering Information (Part Number)

Prefix	Fiber Type	Configuration	Optical Power	Fiber Protection	Fiber Length	Connector ^[1]
PFMS-	50/125, NA 0.22 = A 62.5/125, NA 0.22 = B 105/125, NA 0.22 = C 105/125, NA 0.15 = M Special = 0	Regular = 1	< 5W = 1 10W = 2 50W = 5 100W = 9 Special = 0	3mm = 1 0.9mm = 2 Special = 0	0.5m = 5 1.0m = 1 2.0m = 2 Special = 0	None = 1 SMA = 3 FC/PC = 4 Special = 0

Red color for special order

[1]. The default connector configuration uses fiber with 0.9 mm buffer protection. The connector cannot be installed directly onto bare fiber because the bare fiber is prone to damage during shipping. However, the connector can be assembled on bare fiber if a 3 cm protective loose tube is added for reinforcement. The customer may remove this protective tube after testing. The optical power handling of a standard connector is less than 0.5 W for SMF-28 fiber and decreases further for smaller-core fibers.

+1 781-935-1200

sales@agiltron.com

www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice.
Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.