

Photodiode Extended InGaAs 0.9 – 2.6 μm



DATASHEET

[Return to the Webpage](#)

Features

- 0.9 – 2.6 μm
- Highly Reliable Planar Device
- Low Leakage Current
- High Shunt Resistance
- High Responsivity
- Low Stray Absorption

Applications

- OEM
- Lab user
- Instruments
- Power Monitoring
- Spectral Analysis
- Gas Leak Detection
- Medical Diagnosis
- Covert IR Sensing
- Remote Temperature Sensor

The PDTM Series of Extended-InGaAs Photodiodes provides reliable NIR detection from 0.9 to 2.6 μm with active-area options from 0.3 to 3.0 mm, allowing a clear speed–sensitivity trade-off (smaller areas = lower capacitance and faster response; larger areas = higher sensitivity). For plug-and-play use, an optional driver PCB integrates a low-noise transimpedance amplifier, eliminating external biasing and simplifying bench setup. Standard package and accessory options are available, with custom configurations on request.

Due to their high sensitivity to electrostatic discharge, warranty coverage applies only to fully metal covered modules the benchtops, which include proper protection. Other versions of the lasers and photodetectors are not covered by any warranty. Please use them with great caution.

Specifications ($T_{\text{AMB}} = 23^{\circ}\text{C}$)

Parameter	Min	Typical	Max	Unit
Spectral Range	0.9		2.6	μm
Aperture Size		$\varnothing 950$		μm
Dark Current (@ -0.5 V)		5	15	μA
Shunt Resistance (@ -10 mV)	2	10		$\text{k}\Omega$
Capacitance	1 MHz, 0 V	450	750	pF
	1 MHz, -0.5 V	150	250	
3dB Bandwidth (@ -0.5 V, 50 Ω)	10	15		MHz
Reverse Voltage			1	V
Reverse Current			1	mA
Forward Current			10	mA
Package Type		TO-46		
Responsivity	1.9 μm , 0 V	1.0		A/W
	2.3 μm , 0 V	1.1		
NEP (@ 2.3 μm , 0 V)		1.5	3	$10^{-12}\text{W}/\text{VHz}$
Operation Temperature ^[1]	-40		85	$^{\circ}\text{C}$
Storage Temperature ^[1]	-40		85	$^{\circ}\text{C}$

Note:

[1]. Non-condensing environment

Note: The specifications provided are for general applications with a cost-effective approach. If you need to narrow or expand the tolerance, coverage, limit, or qualifications, please [click this link](#):

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.

Rev 12/05/25

P +1 781-935-1200

E sales@agiltron.com


W www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice. Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.

DATASHEET


Mechanical Dimensions (mm)

Package 1



Note: For detector size 1mm or smaller.

Package 2



Note: For detector size 3mm.

*Product dimensions may change without notice. This is sometimes required for non-standard specifications.


Photodiode Extended InGaAs 0.9 – 2.6 μm




DATASHEET

Typical Curves ($T_{\text{AMB}} = 23^{\circ}\text{C}$)


Dark Current



Dark Capacitance



Responsivity Spectrum



P +1 781-935-1200

E sales@agiltron.com

W www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice. Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.

Photodiode Extended InGaAs 0.9 – 2.6 μm



 DATASHEET

Ordering Information (Part Number)

	26	☐ ☐	1	N	☐ ☐
Prefix	Wavelength	Detector Size	Window	AR Coated	Driver
PDTM-	0.9-2.6 μm = 26	0.3mm = A3 0.5mm = A5 1mm = 10 3mm = 30	Quartz = 1 Spectral Filter = S Sapphire = 2 Non =N	Non = N Yes = 1	No = 00 Yes = 11

Application Notes

Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice.
Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.