

Scanning Fiber Michelson Interferometer

500 – 2600 nm, 0.01 – 1000 mm



DATASHEET

[Return to the Webpage](#)



Features

- Non-Mechanical High Reliability
- Accurate and Reproducible Position Control
- Fast Scan Speeds

Applications

- Laser Phase /Frequency Noise Testing
- Interferometric Sensors
- Heterodyne Interferometer

The MIIM Series Scanning Fiber Optical Michelson Interferometer splits incoming light into two paths using a fiber optic coupler—one reference arm with a fixed fiber length and the other sample arm with a variable length controlled by either a high-speed piezoelectric fiber stretcher or a motor-driven long range delay line. Light reflected from the two fiber reflectors is recombined to produce an interference pattern for high-precision measurements. Fast scanning is achieved via the piezoelectric stretcher driven through a front-panel BNC input, while extended-range scanning is enabled by a motorized stage controlled via USB/GUI. Designed for operation across 500 to 2600 nm with matched single-mode fibers, each MIIM unit features a “zero meter” path mismatch baseline, allowing flexible delay customization. The MIIM is a versatile unit with both optical output or 0-5V electrical output (build in amplified detector). Standard and custom fiber lengths are available, including configurations with variable delay in both arms. The unit comes complete with a power supply.

Specifications

Parameter		Min	Typical	Max	Unit
Center Wavelength		500		2600	nm
Wavelength Range			+/- 150		nm
Insertion Loss ^[1]	1300nm		3	5	dB
	850nm		5	6.5	
	660nm		6	7.5	
Variable Delay Difference	Piezo	0.01		5	mm
	Motor	0.01		500	
Fix Delay Range		1		10000	mm
Path Mismatch (without delay line)				10	mm
Input Power				500	mW
Phase Modulation Speed	Piezo		30		kHz
	Motor		0.01		
Detector Bandwidth (3dB)			DC – 5		MHz
Detector Gain			10 ⁴		V/A
Amplifier Outputs Impedance (SMA)			50		Ω
Power Supply			±12V, 250mA		

Notes:

[1]. Includes connector losses, measured at center wavelength. Shorter wavelength has higher loss

* All accuracy data are valid at 23 ± 5°C and 45 ±15% humidity

Note: The specifications provided are for general applications with a cost-effective approach. If you need to narrow or expand the tolerance, coverage, limit, or qualifications, please [click this link](#):

Rev 11/24/25

P +1 781-935-1200

E sales@agiltron.com

W www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice.
Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.


Scanning Fiber Michelson Interferometer

500 – 2600 nm, 0.01 – 1000 mm




DATASHEET


Functional Diagram



Typical Piezo Stretcher Modulation Frequency Response



Mechanical Dimensions (mm)



P +1 781-935-1200

E sales@agiltron.com

W www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice.

*Product dimensions may change without notice. This is sometimes required for non-standard specifications.

Scanning Fiber Michelson Interferometer


500 – 2600 nm, 0.01 – 1000 mm




DATASHEET

Application Examples


LASER PHASE / FREQUENCY NOISE TESTING



LASER PHASE / FREQUENCY NOISE TESTING 2



FIBER INTERFEROMETRIC SENSOR SIMULATOR



+1 781-935-1200

sales@agiltron.com

www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice. Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.

Scanning Fiber Michelson Interferometer

500 – 2600 nm, 0.01 – 1000 mm



DATASHEET

Ordering Information (Part Number) System

Prefix	Type	Wavelength	Variable Range *	Fix Range	Fiber Type	Fiber Cover	Detector	Connector ^[1]
MIIM-	Standard = 1 Special = 0	488 = 4 532 = 5 650 = 6 780 = 7 850 = 8 980 = 9 1060 = 1 1310 = 3 1550 = C 2000 = 2 Special = 0	0.5mm = 0A 1mm = 01 10mm = 10 20mm = 20 30mm = 30 40mm = 40 50mm = 50 50μm = 05 Special = 00	0.05m = 0A 0.5m = 05 1m = 10 10m = 20 100m = A1 200m = A2 Special = 00	<i>Select below</i>	0.9mm Tube = 1 Special = 0	Non = 1 Yes = 2 Special = 0	FC/PC = 2 FC/APC = 3 SC/PC = 4 SC/APC = 5 ST/PC = 6 LC/PC = 7 LC/APC = 8 LC/UPC = U Special = 0


* < 1mm use high speed piezo actuator, >1mm use motor

[1]. The default connector configuration uses fiber with 0.9 mm buffer protection. The connector cannot be installed directly onto bare fiber because the bare fiber is prone to damage during shipping. However, the connector can be assembled on bare fiber if a 3 cm protective loose tube is added for reinforcement. The customer may remove this protective tube after testing. The optical power handling of a standard connector is less than 0.5 W for SMF-28 fiber and decreases further for smaller-core fibers.

Fiber Type Selection Table

1	SMF-28	5	PM1550	M	MM 50/125μm
		D	PM1950	N	MM 62.5μm
		3	PM1310		
4	SM450	E	PM400		
A	SM1950	F	PM480		
6	SM600	G	PM630		
7	Hi780	H	PM850		
8	SM800	I	PM980		
9	SM980	J	PM780		
B	Hi1060	K	PM460		
C	SM400	L	PM405		

Typical InGaAs Detector Response



P +1 781-935-1200

E sales@agiltron.com

W www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. We reserve the right to change the design or specifications at any time without notice. Agiltron is a registered trademark of Optowares Corporation in the U.S. and other countries.