

Wideband Multimode Circulators 400-900 nm

200 μm Core, 0.22 NA to 400 μm Core, 0.39 NA



DATASHEET

[Return to the Webpage](#)



Features

- Flat Isolation Over 100nm
- Low PMD
- OEM and Custom Build Available
- High Reliability
- Polarization Dependent

Applications

- OCT
- Sensor
- Lab Use
- Instruments

Agiltron's Wideband Multimode Circulators (WMC), designed and manufactured in collaboration with strategic partner, are three-port devices that feature flat spectral response, high efficiency multimode transfer (Port 1 $\rightarrow$ Port 2), and multimode transmission (Port 2 $\leftrightarrow$ Port 3). They can be used to combine multiple signals or illumination / detection channels within a single fiber. The all-fiber WMC is an efficient, versatile, and robust solution for multimode light management with applications in diffuse reflectance spectroscopy, fluorescence spectroscopy, and/or optogenetics.

Specifications

Parameter		Min	Typical	Max	Unit
Wavelength Range		400		900	nm
Transfer Insertion Loss ^{[1], [2]}	Port 1 to 2		≤ 0.8		dB
	Port 2 to 3		≤ 0.8		dB
Transmission Insertion Loss ^{[1], [2]}	Port 3 to 2		≤ 0.5		dB
	Port 1 to 3		≥ 27.0		dB
Directivity ^{[1], [3]}	Port 3 to 1		≥ 34.0		dB
	Port 2 to 1		≥ 12.0		dB
Isolation ^[1]					dB
Max Power Level ^[4]		2 W (with Connectors or Bare Fiber) 4 W (Spliced)			
Port Configuration		2 x 1			
Fiber Lead Length and Tolerance ^[5]		0.8 m $\pm$ 0.075 m / -0.0 m			
Connectors ^{[5], [6]}		2.0 mm Narrow Key FC/PC			
Package Size		$\varnothing 0.23" \times 3.35" (\varnothing 5.8 \text{ mm} \times 85.0 \text{ mm})$			
Jacket		$\varnothing 1.4 \text{ mm}$ Hytrel® Loose Tube *			
Pigtail Tensile Load		10 N			
Operating Temperature		0		60	$^{\circ}\text{C}$
Storage Temperature		-40		85	$^{\circ}\text{C}$

Notes:

- [1]. Specified at room temperature over the bandwidth without connectors using the MWWHF2 LED source.
- [2]. Photodarkening may affect long-term performance at lower wavelengths ($\leq 500 \text{ nm}$).
- [3]. Back reflection of connector surfaces will reduce directivity.
- [4]. Specifies the total maximum power allowed through the component. WMC performance and reliability under high-power conditions must be determined within the user's setup. See Usage Tips for safety and handling information.
- [5]. Additional hydroxyl content, lead lengths and connector options available upon request. Contact us with inquiries.
- [6]. Blue port connector uses ceramic ferrule. White and red port connectors use stainless steel ferrules.

* Hytrel® is a registered trademark of DuPont Polymers, Inc.

Fiber Specifications

Port (Color)	1 (Blue)	2 (White)	3 (Blue)	Unit
Fiber	FG200UEA	FT400UMT		
Core Diameter (Nominal)	200	400		μm
Core NA	0.22	0.39		
Cladding Diameter	220	425		μm
Hydroxyl Content	High OH	High OH		
Bend Radius (Long Term)	≥ 46	≥ 86		mm

Legal notices: All product information is believed to be accurate and is subject to change without notice. Information contained herein shall legally bind Agiltron only if it is specifically incorporated into the terms and conditions of a sales agreement. Some specific combinations of options may not be available. The user assumes all risks and liability whatsoever in connection with the use of a product or its application.

Rev 07/16/25

© Photonwares Corporation

P +1 781-935-1200

E sales@photonwares.com

W www.agiltron.com

Information contained herein is deemed to be reliable and accurate as of the issue date. Photonwares reserves the right to change the design or specifications at any time without notice. Agiltron is a registered trademark of Photonwares Corporation in the U.S. and other countries.

Wideband Multimode Circulators 400-900 nm

200 μm Core, 0.22 NA to 400 μm Core, 0.39 NA



DATASHEET

Port Color Scheme



Usage Tips

1. Before connecting a component to a system, make sure the light source is turned off. Inspect both the input and output fiber ends; debris or contamination on the end face can lead to fiber damage when operated at high powers.
2. After connecting the component, the system should be tested and aligned using a light source at low power. The system power can be ramped up slowly to the desired output power while periodically verifying all components are properly aligned and that coupling efficiency is not changing with respect to optical launch power.
3. Optical connectors can be removed, and the device can be spliced into a setup for operation at higher optical powers. Fiber ends should always be cleaned and cleaved prior to splicing.
4. Multimode optical performance can be sensitive to bend loss and applied pressure. For optimal performance, apply minimal pressure and respect long-term fiber bend radius recommendations.

Ordering Information (Part Number) System

Prefix	Type	Wavelength	Grade	Package	Power	Pass Fiber	Reflector Fiber	Fiber Cover	Connector ^[1]
WBC-	Standard = 1 Special = 0	400-900nm = 1 Special = 0	Regular = 1 Special = 0	Regular = 1 Special = 0	Standard = 1 0.5W = N Special = 0	400/0.39 = 1 Special = 0	200/0.26 = 1 Special = 0	1.4 mm tube = 3 Special = 0	None = 1 FC/PC = 2 Special = 0

* Polarization Independent

** Polarization Dependent

NOTE: Red color for special order

[1]. The default connector configuration uses fiber with 0.9 mm buffer protection. The connector cannot be installed directly onto bare fiber because the bare fiber is prone to damage during shipping. However, the connector can be assembled on bare fiber if a 3 cm protective loose tube is added for reinforcement. The customer may remove this protective tube after testing. The optical power handling of a standard connector is less than 0.5 W for SMF-28 fiber and decreases further for smaller-core fibers.